

LAMPADINE A LED

MINISFERA 6W



Angolo di apertura



Attacco lampada



Potenza equivalente

| CODICE Blister | CODICE Scatola | Potenza → Pot. equivalente (W) | Risparmio energetico | Tensione (V) | Attacco | CRI | Lumen (lm) | Temperatura colore | Dimensioni (mm) |
|----------------|----------------|--------------------------------|----------------------|--------------|---------|------|------------|--------------------|-----------------|
| 499048006 | 499048400 | 6 → 40 | 85% | 220-240 | E14 | > 80 | 470 | 2700 K ● | Ø 45*84 (L) |
| 499048007 | 499048401 | 6 → 41 | 86% | 220-240 | E14 | > 80 | 494 | 4000 K ● | Ø 45*84 (L) |
| 499048008 | 499048402 | 6 → 41 | 86% | 220-240 | E14 | > 80 | 494 | 6000 K ● | Ø 45*84 (L) |



6 kWh / 1000h



Confezione: Blister e Scatola appendibili

MINISFERA 9W PREMIUM



Angolo di apertura



Attacco lampada



Potenza equivalente



Corpo in ceramica



Durata sorgente

| CODICE | Potenza → Pot. equivalente (W) | Risparmio energetico | Tensione (V) | Attacco | CRI | Lumen (lm) | Temperatura colore | Dimensioni (mm) |
|-----------|--------------------------------|----------------------|--------------|---------|------|------------|--------------------|-----------------|
| 499053003 | 9 → 75 | 87% | 170-250 | E14 | > 80 | 900 | 3000 K ● | Ø 45*90 (L) |
| 499053004 | 9 → 75 | 87% | 170-250 | E14 | > 80 | 900 | 4000 K ● | Ø 45*90 (L) |
| 499053005 | 9 → 75 | 87% | 170-250 | E14 | > 80 | 900 | 6000 K ● | Ø 45*90 (L) |



9 kWh / 1000h



Confezione: Scatola appendibile

MINISFERA 6W



Angolo di apertura



Attacco lampada



Potenza equivalente

| CODICE | Potenza → Pot. equivalente (W) | Risparmio energetico | Tensione (V) | Attacco | CRI | Lumen (lm) | Temperatura colore | Dimensioni (mm) |
|-----------|--------------------------------|----------------------|--------------|---------|------|------------|--------------------|-----------------|
| 499048009 | 6 → 40 | 85% | 220-240 | E27 | > 80 | 470 | 2700 K ● | Ø 45*84 (L) |
| 499048010 | 6 → 41 | 86% | 220-240 | E27 | > 80 | 494 | 4000 K ● | Ø 45*84 (L) |
| 499048011 | 6 → 41 | 86% | 220-240 | E27 | > 80 | 494 | 6000 K ● | Ø 45*84 (L) |



6 kWh / 1000h



Confezione: Blister appendibile